



CCTV Installation

Simply call and tell us about the CCTV system you were thinking of installing or already purchased and we will give you a breakdown of costs and any additional equipment if any that may be required. This is a free consultation and with no obligation. Let us deliver peace of mind and expertise that comes with qualified technicians who are the best trained in the business. Call today!

1.888.203.6294



206 N. Towne Avenue

Pomona, CA 91767



SCE 1 Channel Passive Video Balun

Part Number: SCEAV205B

www.securitycamexpert.com

1 Channel

Passive

Video

Balun

Specs

Model	SCEAV205B
Video Bandwidth	DC to 6MHZ
Format	NTSC, PAL,CCIR,SECAM
Common Mode Rejection	70db
Frequency Range	DC-10MHz
Insertion Loss	0.3db
Differential Capacitance	62pF/m max
Distance Using Cat 5 cable	Up to 550M(Black & White), 350M (Color)
Wire Unshielded Twisted Pair Gauge	Cat 2,3, 5 or better 24-16 AWG (0.5-1.31mm)
Impedence BNC Connector Side	75 ohms (unbalanced)
UTP Connector Side	100 ohms (balanced)
DC Loop Resistance	18 ohms per 100m
Environment Temperature	-20 to +70
Humidity (non condensing)	0 to 98%(non-condensing)
Mechanical Mounting	Floating

Features:

- BNC male to terminal block
- Compact Size
- Easier, faster installation of lower cost UTP cable
- Surge Protected
- Max transmit distance 350M (Color) 550M(Black & White)(Passive Receiver)

